

Tipologia / Type of material:

Gres porcellanatonato smaltato/Glazed porcelain stoneware - Group Bla GL - Annex G - EN 14411



Destinazione d'uso del materiale/Intended use of the material:

Piastrelle ceramiche per rivestimenti interni ed esterni / wall tiles for interior and exterior use

FORMATO NOMINALE/NOMINAL SIZE (mm) **1200x1200x9mm, 600x1200x9mm, 600x600x9mm**

SERIE/SERIAL NAME **WALK MATERIALS**

ARTICOLO/ARTICLE **MUD, SALT, SMOKE**

Caratteristiche/Features		Metodo di prova/ Test method	Valori dichiarati/ Declared values
Fisiche/Physical	Assorbimento/Water absorption E _v	 UNI EN ISO 10545-3	≤ 0,5 %
	Forza di rottura/Breaking strength	 UNI EN ISO 10545-4	Sp/Th ≥ 7,5 ≥ 1300 N
	Modulo di rottura/Modulus of rupture	 UNI EN ISO 10545-4	≥ 35 N/mm ²
	Resistenza abrasione superficiale /Resistance to surface abrasion	 UNI EN ISO 10545-7	IV
	Resistenza agli sbalzi termici/Thermal Shock resistance	 UNI EN ISO 10545-9	Resistant
	Resistenza al gelo/Frost resistance	 UNI EN ISO 10545-12	Resistant
	Scivolosità/Determination of slip resistance	 DIN 51130	R10
Chimiche/ Chemical	Reazione al fuoco/Fire reaction	 -	A1 _{fl}
	Resistenza macchie - classe/Stain resistance - class	 UNI EN ISO 10545-14	≥ 5
	Resistenza ai prodotti chimici d'impiego domestico/Resistance to household chemical products	 UNI EN ISO 10545-13	LA

NPD: Nessuna Prestazione Determinata/No Performance Determined